






## DIN blade fuse links for cable and line protection, 500 VAC, gG characteristic

Properties:


- Twin indicator (size 3, 500 A and 630 A with middle indicator)
- Fuse element copper
- Rated voltage: AC 500 V/DC 440 V (Size 000-00 DC 250 V)
- IEC 60269-2
- Breaking capacity: 120 kA (AC 500 V)/25 kA(DC 440 V)

	RATING AMPS	SIZE	STOCK CODE Live metal gripping lugs	PACK QTY	
 <p>Note: DIN 000 size fuses suit DIN 00 switching devices</p>	6	000	NH000KTF-06	3	
	10	000	NH000KTF-10	3	
	16	000	NH000KTF-16	3	
	20	000	NH000KTF-20	3	
	25	000	NH000KTF-25	3	
	32	000	NH000KTF-32	3	
	40	000	NH000KTF-40	3	
	50	000	NH000KTF-50	3	
	63	000	NH000KTF-63	3	
	80	000	NH000KTF-80	3	
	100	000	NH000KTF-100	3	
	125	00	NH00KTF-125	3	
	160	00	NH00KTF-160	3	
		40	1	NH1KTF-040	3
		50	1	NH1KTF-050	3
63		1	NH1KTF-063	3	
80		1	NH1KTF-080	3	
100		1	NH1KTF-100	3	
125		1	NH1KTF-125	3	
160		1	NH1KTF-160	3	
200		1	NH1KTF-200	3	
250		1	NH1KTF-250	3	
		50	2	NH2KTF-050	3
		63	2	NH2KTF-063	3
		80	2	NH2KTF-080	3
		100	2	NH2KTF-100	3
		125	2	NH2KTF-125	3
		160	2	NH2KTF-160	3
	200	2	NH2KTF-200	3	
	250	2	NH2KTF-250	3	
	315	2	NH2KTF-315	3	
	355	2	NH2KTF-355	3	
400	2	NH2KTF-400	3		

	RATING AMPS	SIZE	STOCK CODE Live metal gripping lugs	PACK QTY
	315	3	NH3KTF-315	3
	355	3	NH3KTF-355	3
	400	3	NH3KTF-400	3
	500	3	NH3KTF-500	3
	630	3	NH3KTF-630	3
	800	4A	NH4KTF-800	1
	1000	4A	NH4KTF-1000	1
	1250	4A	NH4KTF-1250	1

	RATING AMPS	SIZE	STOCK CODE Insulated gripping lugs	PACK QTY
	250	2	NH2KTFMK-250	3
	315	2	NH000KTF-315	3
	400	2	NH000KTF-400	3

#### DIN blade solid links-size 00-4a, live metal gripping lugs

	RATING AMPS	SIZE	STOCK CODE Live metal gripping lugs	PACK QTY
	160	00	CSK00	3
	250	1	CSK1	3
	400	2	CSK2	3
	630	3	CSK3	3
	1600	4A	CSK4A	1